



## ECOLINE UNDERCOUNTER RANGE

The **Ecoline range** of glass and dishwashers are the robust, reliable and affordable choice. They guarantee unrivalled accuracy to temperature management and wash results, every cycle.

With easy to use **soft touch controls** and class leading **4 stage filtration** system, Ecoline is the smart, economical choice for all your warewashing requirements, whether a cafe, bar, pub, club, restaurant or care home.



## WHY CHOOSE ECOLINE?

### FEATURES

- Simple soft touch controls
- Choice of 3 wash programs
- 4 stage filtration system
- Powerful wash pump with soft start function
- Generous useable wash height
- Rinse booster pump

### BENEFITS

- Easy to understand and operate
- Offers multiple wash options
- Keeps wash water cleaner and helps prevent blockages in the wash and drain pumps
- Delivers a superior wash without damaging delicate items
- Enables washing of taller glasses and larger plates
- Ensures consistent rinse pressure for sparkling results

**ECOLINE - THE SMART, ECONOMICAL CHOICE**


**TECHNICAL SPECIFICATIONS**
**SPG405UK  
GLASSWASHER**
**SPG505UK  
GLASSWASHER**
**SPD505UK  
DISHWASHER**

Model with integral water softener as standard	SPG405SUK	SPG505SUK	SPD505SUK
Basket size	400x400 mm	500x500 mm	500x500 mm
Machine dimensions (WxDxH)	440x555x695 mm	578x600x811 mm	578x600x811 mm
Cycle times	90, 150, 240 secs	90, 150, 240 secs	90, 150, 240 secs
Maximum baskets per hour	40	40	40
Basket clearance height	300 mm	365 mm	365 mm
Wash pump power rating	0.3kW	0.7kW	0.7kW
Drain pump	✓	✓	✓
Rinse booster pump	✓	✓	✓
Electronic detergent and rinse aid dispensers	✓	✓	✓
KIWA approved break tank	✓	✓	✓
4 stage filtration system	✓	✓	✓
Soft start wash pump	✓	✓	✓
Thermostop, guaranteeing rinse temperature	✓	✓	✓
Double skinned insulated door	✓	✓	✓
Optional freshwater and extended rinse cycles	✓	✓	✓
Optional dual heating temperature management function	✓	✓	✓
Self cleaning cycle	✓	✓	✓
Water consumption per cycle	2.3 L	3.2 L	3.2 L
Electrical specification	230V 1N 50Hz / 13A / 2.9 kW*	230V 1N 50Hz / 30A / 6.8 kW*	230V 1N 50Hz / 30A / 6.8 kW*
	400V 3N 50Hz / 12A / 6.8 kW	400V 3N 50Hz / 12A / 6.8 kW	400V 3N 50Hz / 12A / 6.8 kW
	230V 1N 50Hz / 20A / 4.5 kW	230V 1N 50Hz / 20A / 4.5 kW	230V 1N 50Hz / 20A / 4.5 kW
	230V 1N 50Hz / 15A / 3.4 kW	230V 1N 50Hz / 15A / 3.4 kW	230V 1N 50Hz / 15A / 3.4 kW
	230V 1N 50Hz / 12A / 2.7 kW	230V 1N 50Hz / 12A / 2.7 kW	230V 1N 50Hz / 12A / 2.7 kW
Baskets provided	2x flat baskets (2x PB40G01)	2x flat baskets (2x PB50G02)	1x pegged basket, 1x flat basket, 1x cutlery basket (1x PB50D01, 1x PB50G01 1x PHOOS02)

\* Factory default setting