



TOPLINE UNDERCOUNTER DISHWASHER RANGE

The **Topline range** of undercounter dishwashers are the high specification, reliable and versatile choice. They guarantee unrivalled accuracy to temperature management and wash results, whilst optimising energy and chemical savings, every cycle.

With easy to use **soft touch controls** and dynamic **interlocking 3 stage filtration system**, Topline is the premium and refined choice for all your warewashing requirements, whether for commercial or public sector kitchens.



WHY CHOOSE TOPLINE?

FEATURES

- Simple soft touch controls
- Choice of 7 wash programs
- Interlocking 3 stage filtration system
- Powerful wash pump with soft start function
- Optimal chemical dosing
- Rinse booster pump

BENEFITS

- Easy to understand and operate
- Offers flexible and specific wash options
- Keeps wash water cleaner and helps prevent blockages in the wash and drain pumps
- Delivers a superior wash without damaging delicate items
- Precise measuring of the chemical products
- Ensures consistent rinse pressure for sparkling results

TOPLINE - THE REFINED, PREMIUM CHOICE



**SPD515UK
DISHWASHER**



**SPD512UK
DISHWASHER**



**UD516DUK
DISHWASHER**

TECHNICAL SPECIFICATIONS

Model with integral water softener as standard	SPD515SUK	SPD512SUK	UD516DSUK
Basket size	500x500 mm	500x500 mm	500x500 mm
Machine dimensions (WxDxH)	600x600x820 mm	600x600x820 mm	600x600x820 mm
Cycle times	60, 90, 150, 180, 250, 60, 90 secs	60, 90, 150, 180, 250, 60, 90 secs	60, 90, 150, 180, 250, 60, 90 secs
Maximum baskets per hour	60	40	51
Basket clearance height	415 mm	415 mm	415 mm
Wash pump power rating	0.7 kW	0.7 kW	0.7 kW
Drain pump	✓	✓	✓
Rinse booster pump	✓	✓	✓
Electronic detergent and rinse aid dispensers	✓	✓	✓
KIWA approved break tank	✓	✓	✓
Interlocking 3 stage filtration system	✓	✓	✗
Soft start wash pump	✓	✓	✓
Thermostop, guaranteeing rinse temperature	✓	✓	✓
Optional dual heating temperature management function	✓	✓	✓
Optional freshwater and extended rinse cycles	✓	✓	✓
Self cleaning cycle	✓	✓	✓
Compact pressed wash tank	✓	✓	✓
Water consumption per cycle	3.2 L	3.2 L	3.2 L
Electrical specification	230V 1N 50Hz / 30A / 6.8 kW*	230V 1N 50Hz / 30A / 6.8 kW*	230V 1N 50Hz / 25A / 5.7 kW*
	400V 3N 50Hz / 12A / 6.8 kW	400V 3N 50Hz / 12A / 6.8 kW	400V 3N 50Hz / 12A / 6.8 kW
	230V 1N 50Hz / 20A / 4.5 kW	230V 1N 50Hz / 20A / 4.5 kW	230V 1N 50Hz / 20A / 4.5 kW
	230V 1N 50Hz / 15A / 3.4 kW	230V 1N 50Hz / 15A / 3.4 kW	230V 1N 50Hz / 15A / 3.4 kW
	230V 1N 50Hz / 12A / 2.7 kW	230V 1N 50Hz / 12A / 2.7 kW	230V 1N 50Hz / 12A / 2.7 kW
Baskets provided	1x plate basket, 1x flat basket, 1x cutlery basket (1x PB50D01, 1x PB50G01, 1x PHOOS02)	1x plate basket, 1x flat basket, 1x cutlery basket (1x PB50D01, 1x PB50G01, 1x PHOOS02)	1x plate basket, 1x flat basket, 1x tray basket, 1x flat grid, 1x cutlery basket (1x PB50D01, 1x PB50G01, 1x WB50T03, 1xWG500, 1x PHOOS02)

* Factory default setting