



## TOPLINE HOOD TYPE RANGE

The **Topline range** of hood type dishwashers are the high specification, reliable and versatile choice. They guarantee unrivalled accuracy to temperature management and wash results, whilst optimising energy and chemical savings, every cycle.

With easy to use **soft touch controls** and dynamic **interlocking 3 stage filtration system**, Topline is the premium and refined choice for all your warewashing requirements, whether for commercial or public sector kitchens.



## WHY CHOOSE TOPLINE?

### FEATURES

- Simple hood mounted soft touch controls
- Choice of 7 wash programs
- Interlocking 3 stage filtration system
- Powerful wash pump with soft start function
- Generous useable wash height
- Rinse booster pump

### BENEFITS

- Easy to understand and operate
- Offers flexible and specific wash options
- Keeps wash water cleaner and helps prevent blockages in the wash and drain pumps
- Delivers a superior wash without damaging delicate items
- Enables washing of larger plates and utensils
- Ensures consistent rinse pressure for sparkling results

TOPLINE - THE REFINED, PREMIUM CHOICE



## TECHNICAL SPECIFICATIONS

**SPH515  
DISHWASHER**

**SPH515S  
DISHWASHER**

Integral water softener with salt management system	x	✓
Basket size	500x500 mm	500x500 mm
Machine dimensions (WxDxH)	635x750x1510/2102 mm	635x750x1510/2102 mm
Cycle times	60, 90, 150, 180, 250, 420, 60 secs	60, 90, 150, 180, 250, 420, 60 secs
Maximum baskets per hour	60	60
Basket clearance height	470 mm	470 mm
Wash pump power rating	0.7 kW	0.7 kW
Drain pump	✓	✓
Rinse booster pump	✓	✓
Electronic detergent and rinse aid dispensers	✓	✓
KIWA approved break tank	✓	✓
Interlocking 3 stage filtration system	✓	✓
Soft start wash pump	✓	✓
Thermostop, guaranteeing rinse temperature	✓	✓
Optional dual heating temperature management function	✓	✓
Optional freshwater and extended rinse cycles	✓	✓
Self cleaning cycle	✓	✓
Compact 14 L pressed wash tank	✓	✓
Water consumption per cycle	2.7 L	2.7 L
Electrical specification	400V 3N 50Hz / 16A / 9.7 kW*	400V 3N 50Hz / 16A / 9.7 kW*
	230V 1N 50Hz / 30A / 6.7 kW	230V 1N 50Hz / 30A / 6.7 kW
	230V 1N 50Hz / 16A / 3.7 kW	230V 1N 50Hz / 16A / 3.7 kW
Baskets provided	1x pegged basket, 1x flat basket, 1x cutlery basket (1x PB50D01, 1x PB50G02 1x PHOOS02)	1x pegged basket, 1x flat basket, 1x cutlery basket (1x PB50D01, 1x PB50G02 1x PHOOS02)

\* Factory default setting